

TS107

Tool & Bench Cleaner

Description

Robnor Resinlab are formulators and suppliers of protective coatings for electrical and electronic components
Designers and builders of equipment for resin handling and application

TS107 Resin Remover

TS107 Tool and Bench cleaner is a formulation that will clean uncured epoxy resins, allowing their removal from most surfaces. TS107 thus allows the removal of accidental deposits of uncured resins from production equipment such as tools, jigs and fixtures, and machine parts as well as work surfaces and floors. TS107 has medium volatility and will evaporate in ambient conditions. The material is non-toxic and therefore lends itself to use in a wide array of applications.

Procedure

Uncured resin can be removed from components with a clean cloth, which has been wetted with TS107
Any materials that have been contaminated with uncured resin or hardener must be disposed of as per the material Health & Safety data sheet

Operating precautions

The solvent is highly flammable, so due care and attention must be exercised when using this product.
Good workroom ventilation should be maintained.
TS107 should be stored in a cool place away from direct sunlight.

Personal precautions

Anyone handling TS107 should protect the eyes against splashes by wearing safety glasses or goggles.
If inadequate precautions should allow solvent to reach the eyes, copious rinsing with fresh water should be carried out immediately and continued for not less than 15 minutes, after which examination by a doctor is advisable.
Skin contact also should be avoided: polythene gloves are recommended.

Approvals

RoHS compliant	Yes
UL94 V-0	No
REACH (SVHC concentration)	0%

Availability

Available through distribution www.resins-online.com and sales@robnor.co.uk

Part Numbers

TS107/NC/1LT

Storage and Shelf Life

Come within the Highly Flammable Liquids Regulations 1972 and the Petroleum Consolidated Act 1928.

Health and Safety

Anyone handling TS107 should protect the eyes against splashes by wearing safety glasses or goggles. If inadequate precautions should allow solvent to reach the eyes, copious rinsing with fresh water should be carried out immediately and continued for not less than 15 minutes, after which examination by a doctor is advisable. Skin contact also should be avoided: polythene gloves are recommended. On account of the halogenated material in TS107, workers in an atmosphere containing TS107 vapour must be instructed to refrain from smoking. In the event of an abnormal increase in the concentration of TS107 vapour in the workroom atmosphere - e.g., through accidental process spillage - anyone showing signs of drowsiness as a result of this should be removed to a fresh-air zone immediately and first-aid measures should be applied as indicated in the TS107 Safety Data Sheet.

Copyright & Warranty - Robnor ResinLab Limited

The results and information above does not constitute a specification and is given in good faith and without warranty. The information is derived from test/or extrapolations believed to be reliable and is quoted for guidance only. The product is offered for evaluation on the understanding the customer satisfies himself that the product is suitable for the intended application by proper evaluation and testing.

Contact Details

Robnor ResinLab Limited
31 Athena Avenue
Elgin Industrial Estate
Swindon
SN2 8EJ
United Kingdom

Tel: +44 (0) 1793 823741
Fax: +44 (0) 1793 827033
Email: support@robnor.co.uk
Web: www.robnor-resinlab.com
Buy Online: www.resins-online.com (UK only)